



**SHUTTERMAX®**  
**HCS**

**MAXimum Security, High Cycle, Ventilation and Whisper-Quiet Operation**

The German designed **SHUTTERMAX® HCS** is perfect for carpark applications where high cycle and quiet operation is needed. The unique design of the rollformed aluminium profile provides light weight strength coupled with low operating noise and is corrosion resistant.

**AUSTRALIAN MADE**  
**EUROPEAN DESIGNED**  
**GERMAN DRIVE TECHNOLOGY**






Single Wall Perforated Profile



Guide with Wear Strip



Double Wall Insulated Profile



GFA Safedrive®

## Technical Datasheet – SHUTTERMAX® HCS

Application	External / Internal / High Cycle	
Dimension	Max width	6500mm
	Max height	3000mm
Opening Speed	Up to	0.4m/sec
Closing Speed		0.15m/sec
Door Curtain	Mill Finish Aluminium	Standard
	Powdercoated	Optional
	Double Wall Insulated Profile	Optional
Door Guides	Galvanised Steel	Standard
	Powdercoated	Optional
Top Roll Tube	Galvanised Steel	Standard
Drive System	GfA Safedrive® with integrated safety brake	Standard
	GfA VSD Safedrive® with integrated safety brake	Optional
Safety	Safedrive® integrated safety brake	Standard
	Door-line Safety Light Curtain (1800mm active)	Standard
	Emergency Stop Button	Standard
	Manual Chain Over-ride	Standard
Wind Load Rating	Gusts > 90km/hr (Class 2)	Standard



**MAX Door Solutions Pty. Ltd.**

**P: 1300 793 378**

[sales@maxdoors.com.au](mailto:sales@maxdoors.com.au)

56 Export Drive, Molendinar, QLD, 4214

PO Box 777, Biggera Waters QLD, 4216

[www.maxdoors.com.au](http://www.maxdoors.com.au)